

Listing of Claims:

Claims 1-17 (Canceled).

18. (Currently Amended) An interior member for a cab of a work vehicle, comprising:

a foundation body panel which has a first side and a second side, and which comprises a plurality of ribs at the second side, at least one space being defined by the ribs at the second side of the foundation body panel;

an outer layer material provided at the first side of the foundation body panel;

a first sound absorbing member comprising a sound absorbing material provided between the outer layer material and the first side of the foundation body panel;

a second sound absorbing member ~~comprising~~ formed by filling a sound absorbing material ~~provided~~ in at least one said space defined by the ribs at the second side of the foundation body panel; and

a metal plate provided at the second side of the foundation body panel, wherein the foundation body panel is fastened to the metal plate.

Claim 19 (Canceled).

20. (Previously Presented) The interior member according to claim 18, wherein at least a plurality of the ribs of the foundation body panel cross each other.

21. (Previously Presented) An interior member for a cab of a work vehicle, comprising:

- a foundation body panel which has a first side and a second side, and which comprises a plurality of ribs at the second side, at least one space being defined by the ribs at the second side of the foundation body panel;

- an outer layer material provided at the first side of the foundation body panel;

- a sound absorbing member comprising a sound absorbing material provided between the outer layer material and the first side of the foundation body panel; and

- a metal plate provided at the second side of the foundation body panel, wherein the foundation body panel is fastened to the metal plate;

- wherein the foundation body panel comprises a portion for attaching an electrical wire member channel at the second side of the foundation body panel.

22. (Previously Presented) An interior member for a cab of a work vehicle, comprising:

5 a foundation body panel which has a first side and a second side, and which comprises a plurality of ribs at the second side, at least one space being defined by the ribs at the second side of the foundation body panel;

an outer layer material provided at the first side of the foundation body panel;

10 a sound absorbing member comprising a sound absorbing material provided between the outer layer material and the first side of the foundation body panel; and

a metal plate provided at the second side of the foundation body panel, wherein the foundation body panel is fastened to the metal plate;

15 wherein the foundation body panel is made of a material having heat insulating properties, and wherein the foundation body panel comprises a portion for forming an air conditioning duct at the second side of the foundation body panel.

23. (Previously Presented) The interior member according to claim 22, further comprising a closing member which closes a space at least partially defined by the portion for forming the air conditioning duct, wherein the closing member and the portion for forming the air conditioning duct together form the air conditioning duct.

Claims 24 and 25 (Canceled).

26. (Previously Presented) The interior member according to claim 18, wherein the sound absorbing material of the second sound absorbing member comprises at least one of: polyurethane foam, glass wool, PET wool and wool made of at least one recycled plastic material.

27. (Previously Presented) The interior member according to claim 18, wherein the first sound absorbing member has a thickness of 5 mm to 20 mm.

Claims 28 and 29 (Canceled)

30. (Currently Amended) ~~The~~ An interior member ~~according to claim 19, further~~ for a cab of a work vehicle, comprising:
a foundation body panel which has a first side and a second side, and which comprises a plurality of ribs at the second side,
at least one space being defined by the ribs at the second side of the foundation body panel;
an outer layer material provided at the first side of the foundation body panel;

a sound absorbing member comprising a sound absorbing material provided between the outer layer material and the first side of the foundation body panel;

a metal plate provided at the second side of the foundation body panel, wherein the foundation body panel is fastened to the metal plate; and

a further sound absorbing member comprising a sound absorbing material provided on an opposite side of the metal plate with respect to the foundation body panel, such that the metal plate is provided between the further sound absorbing member and the foundation body panel;

wherein at least a plurality of the ribs of the foundation body panel cross each other.

Claims 31-33 (Canceled).

34. (Currently Amended) A wall member for a cab of a work vehicle, comprising:

(i) an outer metal plate; and

(ii) an interior member which is mounted to the outer metal plate, wherein the interior member comprises:

a foundation body panel which has a first side and a second side, and which comprises a plurality of ribs at the second side, at least one space being defined by the ribs at the

second side of the foundation body panel, wherein the second side
10 of the foundation body panel is mounted on the outer metal plate
such that the outer metal plate closes the at least one space
defined by the ribs;

an outer layer material provided at the first side of
the foundation body panel;

15 a first sound absorbing member comprising a sound
absorbing material provided between the outer layer material and
the first side of the foundation body panel; and

a second sound absorbing member ~~comprising~~ formed by
filling a sound absorbing material ~~provided~~ in at least one said
20 space defined by the ribs and closed by the outer metal plate at
the second side of the foundation body panel.

35. (Currently Amended) The wall member according to
claim 34, further comprising a first exterior layer provided on
the outer metal plate on an opposite side of the metal plate with
respect to the interior member, such that the outer metal plate
5 is provided between the first exterior layer and the interior
member.

36. (Previously Presented) The wall member according to
claim 35, further comprising a second exterior layer provided on
the first exterior layer, wherein the second exterior layer

comprises one of a paint film and a resin layer that includes
5 paint.

37. (Previously Presented) A wall member for a cab of a
work vehicle, comprising:

(i) an outer metal plate; and

(ii) an interior member which is mounted to the outer metal
5 plate, wherein the interior member comprises:

an inner metal plate, which is mounted on the outer
metal plate with a space provided between the inner metal plate
and the outer metal plate;

a foundation body panel which has a first side and a
10 second side, and which comprises a plurality of ribs at the
second side, at least one space being defined by the ribs at the
second side of the foundation body panel, wherein the second side
of the foundation body panel is mounted on the inner metal plate
such that the inner metal plate closes the at least one space
15 defined by the ribs and such that the inner metal plate is
positioned between the foundation body panel and the outer metal
plate;

an outer layer material provided at the first side of
the foundation body panel; and

20 a first sound absorbing member comprising a sound
absorbing material provided between the outer layer material and
the first side of the foundation body panel.

38. (Previously Presented) The wall member according to
claim 37, further comprising a second sound absorbing member
comprising a sound absorbing material provided in at least one
said space defined by the ribs and closed by the inner metal
5 plate at the second side of the foundation body panel.

39. (Previously Presented) The wall member according to
claim 37, further comprising a further sound absorbing member
comprising a sound absorbing material provided in the space
between the inner metal plate and the outer metal plate.

Claims 40 and 41 (Canceled).